


S.No.	DESCRIPTION	QTY.	MATERIAL
1	BODY	1	ASTM B62/B61/B148
2	SIDE COVER	1	ASTM B62/B61/B148
3	BALL	1	ASTM B62/B61/B148
4	SEAT	2	RPTFE
5	BODY SEAL	1	GRAFOIL/PTFE/VITON
6	BODY STUD	AS	ASTM A 193 Gr.B7/B7M/A 320 Gr. L7
	BODY STUD NUT	REQD.	ASTM A 194 Gr.2H /2HM/Gr. 4
7	STEM	1	NI-AL BRONZE B148 UNS C95800
8	GLAND PACKING	-	GRAFOIL/PTFE/VITON
9	GLAND	1	BS 2874 CA 104 AB2/COPPER ALLOY
10	STEM SEAL	1	PTFE/VITON/CFT
11	GLAND NUT	1	BS 2874 CA 104 AB2/COPPER ALLOY



DETAILS-'A'
ANTISTATIC DEVICE

TEST PRESSURE PSig			
CLASS	HYDROSTATIC	AIR	
150	BODY	SEAT	SEAT
	425	300	80

DESIGN FEATURES	
DESIGN AND DIMENSIONS	API-6D
ENDS FLANGE DIMENSIONS	A.N.S.I. B 16.5
TESTING	API-6D
FIRE SAFE	API-6FA

'N' NOS, ØH HOLES ON 'P' P.C.D.
EQUISPACED & OFFCENTRED

ALL BELOW SPECIFICATIONS ARE FOR INFORMATORY PURPOSE ONLY.
AND ARE SUBJECT TO CHANGE WITHOUT PRIOR NOTICE.

16"	610	303	482.6	25.4	12	431.8	470	36.5
14"	533	252	406.4	25.4	12	362	413	35
12"	610	303	482.6	25.4	12	431.8	381	31.8
10"	533	252	406.4	25.4	12	362	323.9	30.2
8"	457	201	342.9	22.2	8	298.5	269.7	28.4
6"	394	150	279.4	22.2	8	241.3	215.9	25.4
4"	229	100	228.6	19.1	8	190.5	157.2	23.9
3"	203	74	190.5	19.1	4	152.4	127	19.1
2"	178	49	152.4	19.1	4	120.7	92	15.8
SIZE NB	'A'	'ØB'	'ØD'	'ØH'	'N'	'ØP'	'ØR'	'T'

NOTES: -

VALVE SIZE 2" TO 6" - LEVER/WRENCH OPERATED
ABOVE 6" - GEAR OPERATED

DESCRIPTION	
Ni-AL. BRONZE 2 PIECE (R.B.) BALL VALVE FLOATING HANDLE OPERATED CLASS:-150 SIZE:- 2" TO 12"	
DRN:	FORWARD ALLOYS AND CASTINGS L.B.S. MARG, BHANDUP BOMBAY
DATE:	
CHKD:	
DATE:	
APPD:	
DATE:	
DRAWING NO.:	