


S.No.	DESCRIPTION	QTY.	MATERIAL
1	BODY	1	ASTM B62/B61/B148
2	SIDE COVER	1	ASTM B62/B61/B148
3	BALL	1	ASTM B62/B61/B148
4	SEAT	2	RPTFE
5	BODY SEAL	1	GRAFOIL/PTFE/VITON
6	BODY STUD	AS	ASTM A 193 Gr.B7/B7M/A 320 Gr. L7
	BODY STUD NUT	REQD.	ASTM A 194 Gr.2H /2HM/Gr. 4
7	STEM	1	NI-AL BRONZE B148 UNS C95800
8	GLAND PACKING	-	GRAFOIL/PTFE/VITON
9	GLAND	1	BS 2874 CA 104 AB2/COPPER ALLOY
10	STEM SEAL	1	PTFE/VITON/CFT
11	GLAND NUT	1	BS 2874 CA 104 AB2/COPPER ALLOY



TEST PRESSURE PSIG			
CLASS	HYDROSTATIC	AIR	
150	BODY	SEAT	SEAT
	425	300	80

DESIGN FEATURES	
DESIGN AND DIMENSIONS	API-6D
ENDS FLANGE DIMENSIONS	A.N.S.I. B 16.5
TESTING	API-6D
FIRE SAFE	API-6FA

'N' NOS, øH HOLES ON 'P' P.C.D.
EQUISPACED & OFFCENTRED
DETAILS-'A'
ANTISTATIC DEVICE

ALL BELOW SPECIFICATIONS ARE FOR INFORMATORY PURPOSE ONLY.
AND ARE SUBJECT TO CHANGE WITHOUT PRIOR NOTICE.

2"	178	51	152.5	19	4	120.5	92	16
1½"	165	38	127	16	4	98.5	73	14.5
1"	127	25	108	16	4	79.5	51	11.2
¾"	118	20	98	16	4	70	43	10.5
½"	108	12.7	89	16	4	60.5	35	10
SIZE NB	'A'	'øB'	'øD'	'øH'	'N'	'øP'	'øR'	'T'

DESCRIPTION	
Ni-AL. BRONZE 3 PIECE (R.B.) BALL VALVE FLOATING HANDLE OPERATED CLASS:-150 SIZE:- ½" TO 2"	
DRN:	FORWARD ALLOYS AND CASTINGS L.B.S. MARG, BHANDUP BOMBAY
DATE:	
CHKD:	
DATE:	
APPD:	
DATE:	
DRAWING NO.:	